

VU Research Portal

Exponentially better than brute force: Solving the job-shop scheduling problem optimally by dynamic programming

Gromicho Dos Santos, J.A.; van Hoorn, J.J.; Saldanha-da-Gama, F.; Timmer, G.T.

2009

document version

Early version, also known as pre-print

[Link to publication in VU Research Portal](#)

citation for published version (APA)

Gromicho Dos Santos, J. A., van Hoorn, J. J., Saldanha-da-Gama, F., & Timmer, G. T. (2009). *Exponentially better than brute force: Solving the job-shop scheduling problem optimally by dynamic programming*. (Research Memorandum; No. 2009-56). Faculteit der Economische Wetenschappen en Bedrijfskunde.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal ?

Take down policy

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

E-mail address:

vuresearchportal.ub@vu.nl

Exponentially better than brute force: solving the job-shop scheduling problem optimally by dynamic programming

Research Memorandum 2009-56

**Joaquim A.S. Gromicho
Jelke J. van Hoorn
Francisco Saldanha-da-Gama
Gerrit T. Timmer**

Exponentially better than brute force: solving the job-shop scheduling problem optimally by dynamic programming

Joaquim A. S. Gromicho

Vrije Universiteit, Amsterdam, The Netherlands & ORTEC, Gouda, The Netherlands
email: jgromicho@feweb.vu.nl

Jelke J. van Hoorn

Vrije Universiteit, Amsterdam, The Netherlands & ORTEC, Gouda, The Netherlands
email: jhoorn@feweb.vu.nl

Francisco Saldanha-da-Gama

Faculdade de Ciências & Centro de Investigação Operacional, Universidade de Lisboa, Portugal
email: fsgama@fc.ul.pt

Gerrit T. Timmer

Vrije Universiteit, Amsterdam, The Netherlands & ORTEC, Gouda, The Netherlands
email: Gerrit.Timmer@ortec.com

Scheduling problems received substantial attention during the last decennia. The job-shop problem is a very important scheduling problem, which is NP-hard in the strong sense and with well-known benchmark instances of relatively small size which attest the practical difficulty in solving it. The literature on job-shop scheduling problem includes several approximation and optimal algorithms. So far, no algorithm is known which solves the job-shop scheduling problem optimally with a lower complexity than the exhaustive enumeration of all feasible solutions. We propose such an algorithm, based on the well-known Bellman equation designed by Held and Karp to find optimal sequences and which offers the best complexity to solve the Traveling Salesman Problem known to this date. For the TSP this means $\mathcal{O}(n^2 2^n)$ which is exponentially better than $\mathcal{O}(n!)$ required to evaluate all feasible solutions. We reach similar results by first recovering the principle of optimality, which is not obtained for free in the case of the job-shop scheduling problem, and by performing a complexity analysis of the resulting algorithm. Our analysis is conservative but nevertheless exponentially better than brute force. We also show very promising results obtained from our implementation of this algorithm, which seem to indicate two things: firstly that there is room for improvement in the complexity analysis (we observe the generation of a number of solutions per state for the benchmark instances considered which is orders of magnitude lower than the bound we could devise) and secondly that the potential practical implications of this approach are at least as exciting as the theoretical ones, since we manage to solve some celebrated benchmark instances in processing times ranging from seconds to minutes.

Key words: job-shop scheduling; dynamic programming; complexity analysis

MSC2000 Subject Classification: Primary: 90B35, 90C39; Secondary: 68W40

OR/MS subject classification: Primary: deterministic scheduling, dynamic programming; Secondary: analysis of algorithms

1. Introduction. In a job-shop scheduling problem n jobs have to be processed by m dedicated machines. Each job has to visit all the machines following a specific order. The time each job requires in each machine depends on the job and on the machine and it is assumed to be known in advance. The jobs can not overlap in the machines and no job can be processed simultaneously by two or more machines. Preemption is not allowed. The goal is to schedule the jobs so as to minimize the makespan, which is the maximum of their completion time.

The job-shop scheduling problem is one of the most studied combinatorial optimization problems. Nevertheless, it still remains a very challenging problem to solve optimally. From a complexity point of view, the problem is NP-hard (Lenstra and Rinnooy Kan [21]). Lenstra et al. [22] show that even some ‘simplified’ versions are NP-hard. These include 3 machines and 3 jobs; 2 machines and no more than 3 operations per job (in this case a job may have to visit a machine more than once); 3 machines and no more than 2 operations per job; 3 machines and unitary processing times. Nevertheless, some particular cases of the job-shop scheduling problem are polynomial, such as the problem with 2 machines and no more than 2 operations per job (Jackson [14]) and the problem with 2 machines and unitary processing times (Hefetz and Adiri [12]).

Among the methodologies that have been considered for tackling the job-shop scheduling problem we

can distinguish exact procedures (working for instances with a rather limited size), heuristic procedures and polynomial time approximation algorithms.

To the best knowledge of the authors, all the exact algorithms that have been proposed for the job-shop scheduling problem are branch-and-bound procedures. Without being exhaustive we can cite the works of Applegate and Cook [3], Brucker et al. [4], Carlier and Pinson [5], Lageweg et al. [17] and Martin and Shmoys [24].

Many heuristic approaches have been proposed in the literature for obtaining good quality solutions to the job-shop scheduling problem. A well-known procedure is the so-called shifting bottleneck procedure by Adams et al. [1]. Genetic algorithms were proposed by Croce et al. [6] and Dorndorf and Pesch [7]. Van Laarhoven et al. [30] and Steinhöfel et al. [28] proposed simulated annealing procedures for obtaining feasible solutions to the problem. A tabu search procedure was proposed in the works by Taillard [29] and Nowicki and Smutnicki [25]. Recently, Zhang et al. [33] proposed a new hybrid approach combining tabu search and simulated annealing, which proved to be very efficient for finding optimal or near-optimal solutions for many benchmark instances of the problem. Rego and Duarte [26] proposed a procedure that combines the basic shifting bottleneck procedure by Adams et al. [1] with a dynamic and adaptive neighborhood search procedure based on the so-called filter-and-fan method.

As far as the polynomial time approximation algorithms are concerned, Shmoys et al. [27] propose a procedure with a performance guarantee $O(\frac{\log(m\mu) \log(\min(m\mu, p_{\max}))}{\log \log(m\mu)})$ for a job-shop scheduling problem in which a job may have to return more than once to each machine. $p_{\max} = \max_{ij} p_{ij}$, m is the number of machines and μ denotes the maximum number of operations over all jobs. When each job has to visit each machine exactly once, the factor μ can be ignored in the performance guarantee. Goldberg et al. [10] improve the above performance by presenting a polynomial time approximation algorithm with a performance guarantee $O(\frac{\log(m\mu) \log(\min(m\mu, p_{\max}))}{\log \log(m\mu)^2})$. For the case in which each job visits at most once each machine the above performance is still improved by Feige and Scheideler [8] who provide an approximation guarantee $O(m\mu \log(m\mu) \log \log(m\mu))$. For a fixed number of machines and also for a fixed maximum number of operations per job, Shmoys et al. [27] present a $2 + \epsilon$ approximation algorithm. Jansen et al. [16] improve the previous performance guarantee. Leighton et al. [19] and Leighton et al. [20] propose polynomial time approximation algorithms with constant performance guarantee for the job shop scheduling problem with unitary processing times assuming that each job has to be processed exactly once on each machine.

Unlike the above mentioned complexity results about approximations, little seems to be known about the complexity of optimal algorithms for many NP-hard problems. Woeginger [31] stresses the importance of such algorithms and points out that for many such problems it is possible to do better than ‘brute force’. In particular, for a single machine scheduling problem, an algorithm based on dynamic programming is mentioned. This algorithm follows along the lines of the celebrated work by Held and Karp [13] for the Traveling Salesman Problem, which offers still to this date the best complexity of an optimal algorithm for the TSP (see Woeginger [32]).

In the case of the job-shop scheduling problem, the decision to be made regards the order by which the n jobs will be processed on each of the m machines. Accordingly, a brute-force enumerative algorithm for the problem has worst-case complexity $O((n!)^m)$, which is lower than the worst-case complexity for branch-and-bound algorithms.

In this paper we present an exact algorithm for the job-shop scheduling problem with a complexity that we can prove to be $O((2p_{\max})^{n-1} (n\sqrt{n} + (2p_{\max})^2) (m+1)^n n)$, which is exponentially lower than brute-force. The new algorithm is based on dynamic programming. We show that for the job-shop scheduling problem a straightforward application of the Held and Karp equation is not possible because the optimality principle does not hold. Nevertheless, we show that it is possible to redefine the state space and adjust the Belman equation accordingly, in order to recover the optimality principle.

The remainder of the paper is organized as follows. In the next section we present some background which includes notation, definitions and basic properties of the problem. In section 3 we present the new algorithm. Section 4 is devoted to a complexity analysis. In Section 5 some computational tests performed with the new procedure are presented and discussed. The paper ends with a conclusion about the research done.

2. Notation, definitions and basic properties. Consider the job-shop scheduling problem as defined in the previous section. Let $\mathcal{J} = \{j_1, j_2, \dots, j_n\}$ denote the set of jobs and $\mathcal{M} = \{m_1, m_2, \dots, m_m\}$ the set of machines. p_{ij} stands for the processing time of job $j \in \mathcal{J}$ on machine $i \in \mathcal{M}$. A job consists of m task operations each of which associated with a specific machine. The sequence of operations for each job $j \in \mathcal{J}$ is denoted by $\pi_j(1), \dots, \pi_j(m)$ that is, for job $j \in \mathcal{J}$, $\pi_j(i)$ is the i -th machine that job j has to visit. $\mathcal{O} = \{o_1, o_2, \dots, o_{n \times m}\}$ is the set of operations. The first n operations refer to the first operation of each job (in the order of the jobs), operations o_{n+1}, \dots, o_{2n} concern the second operation of the n jobs, and so on. For an operation $o \in \mathcal{O}$ we denote by $j(o)$ and $m(o)$ the corresponding job and machine, respectively. Note that $j(o_i) = i \bmod n$. We denote by $p(o)$ the processing time of operation $o \in \mathcal{O}$. Note that $p(o) = p_{m(o)j(o)}$.

DEFINITION 2.1 A schedule is a function $\psi : \mathcal{O} \longrightarrow \mathbb{N} \cup \{0\}$ such that for each operation $o \in \mathcal{O}$, $\psi(o)$ gives the starting time of operation o . A schedule ψ is said to be feasible if:

- (i) $\psi(o) \geq 0$, $o \in \mathcal{O}$;
- (ii) $\forall o_k, o_l \in \mathcal{O}$ such that $j(o_k) = j(o_l)$ and $k < l$ one has $\psi(o_k) + p(o_k) \leq \psi(o_l)$;
- (iii) $\forall o_k, o_l \in \mathcal{O}$ such that $o_k \neq o_l$ and $m(o_k) = m(o_l)$ we have $\psi(o_l) + p(o_l) \leq \psi(o_k) \vee \psi(o_k) + p(o_k) \leq \psi(o_l)$.

The goal in a job-shop scheduling problem is to find the feasible schedule with the minimum makespan that is, the feasible schedule ψ which minimizes $\max_{o \in \mathcal{O}} \{\psi(o) + p(o)\}$. In this study we consider the value 0 for the origin of time.

For every feasible schedule for the job-shop scheduling problem it is possible to associate a sequence of operations where the order of the operations processed on a single machine as well as the order defined for each job is preserved. One example of such type of sequence is obtained by sorting all operations by their starting time in the schedule considered. However, one single sequence of operations defines an infinite number of schedules (e.g. all those obtained by the addition of positive constants to the starting time of all operations). On the other hand, not all the sequences define a feasible solution. In fact, even if a sequence preserves the order of operations given for each job, it may create a dead-lock.

Hereafter, we will be interested only in sequences that correspond to feasible solutions to the problem that is, feasible sequences. For the sake of simplicity, in the remainder of the paper we will omit the word “feasible” every time we refer to a sequence.

Given a sequence of operations of a job-shop scheduling problem, we can obtain the schedule that results from starting all the operations as soon as possible in the order defined by the sequence and keeping feasibility. This is the (unique) schedule which has the minimum makespan among all the schedules that can be associated to the sequence. Hereafter, we will be interested only in such schedules.

Note that different sequences of operations can lead to the same schedule. Figure 1 depicts a feasible solution for a small instance of the job-shop scheduling problem. The schedule associated with this solution can be obtained from the following feasible sequences: $o_1 o_2 o_3 o_4$, $o_1 o_2 o_4 o_3$, $o_2 o_1 o_3 o_4$ and $o_2 o_1 o_4 o_3$. This small example makes it clear that there is not a one to one correspondence between feasible schedules and sequences of operations. The following result defines a unique sequence for every schedule.




Figure 1: An illustrative schedule

PROPOSITION 2.1 For every feasible solution for the job-shop scheduling problem there is one and only one sequence of operations defining the schedule such that the completion time of the operations along the sequence is non decreasing and in which the order of the machines is increasing for two consecutive operations with equal completion time.

PROOF. Consider a feasible solution for the job-shop scheduling problem. A sequence of operations featuring the conditions stated is obtained by sorting the operations non-decreasingly in terms of their completion time and for those that have an equal completion time, by sorting them in increasing order

of the machine associated with them. The total lexicographic order imposed on this sequence assures unicity. \square

An immediate consequence of the previous proposition is stated in the following corollary.

COROLLARY 2.1 *For an optimal solution of the job-shop scheduling problem there exists one and only one sequence featuring the conditions stated in proposition 2.1.*

With the purpose of building (feasible) sequences (and eventually the optimal sequence) to a job-shop scheduling problem, the operations can be iteratively added to the sequence. Before all the operations are in the sequence, we have an incomplete or partial sequence which we define formally as follows.

DEFINITION 2.2 *A partial sequence is a sequence of operations defined by the first k operations of a sequence for any $k = 0, \dots, |\mathcal{O}|$.*

For a partial sequence T we denote by $C_{\max}(T)$ the corresponding (partial) makespan, which is the maximum completion time for the operations scheduled in the order of the sequence.

DEFINITION 2.3 *If T_1 and T_2 are two partial sequences involving the same set of operations, we say that T_2 dominates T_1 if $C_{\max}(T_2) \leq C_{\max}(T_1)$.*

DEFINITION 2.4

1. *An ordered sequence is a sequence ordered as stated in proposition 2.1.*
2. *An ordered partial sequence is a sequence defined by the first k operations of an ordered sequence for any $k = 0, \dots, |\mathcal{O}|$.*
3. *A sequence or a partial sequence not ordered as stated in proposition 2.1 is called unordered.*

It is straightforward to conclude that any unordered partial sequence can be converted into an ordered partial sequence with the same makespan. In fact, reordering the operations as stated in proposition 2.1 does not increase the makespan.

DEFINITION 2.5 *Let $S \subseteq \mathcal{O}$ denote a subset of operations such that at least one ordered partial sequence can be associated to it. Let T denote an ordered partial sequence that can be associated to S .*

1. *Any set of operations obtained by adding to S one operation that is not in S but such that all the operations that precede it in the same job are already in S is called an expansion of S .*
2. *A partial sequence that is obtained by adding to the end of T one operation o that can be used to expand S is called an expansion of the ordered partial sequence T with o . Let $T + o$ denote such expansion.*
3. *Every partial sequence can be progressively expanded leading to a full sequence of operations thus defining a feasible solution. Such final sequence is called a completion of the initial partial solution.*

REMARK 2.1 *A subset of operations $S \subset \mathcal{O}$ has no (ordered) partial sequence associated with it when for some job an operation is in S while one of the preceding operations of the same job is not in S .*

Hereafter we consider only subsets of operations $S \subseteq \mathcal{O}$ such that at least one ordered partial sequence can be associated to them.

It should be noted that the expansion of an ordered partial sequence does not necessarily lead to a new ordered partial sequence. That is the case when the operation selected to join the sequence has an earliest completion time lower than the makespan of the partial sequence.

The job-shop scheduling problem can now be defined as the problem of finding the ordered sequence of operations which leads to the minimum makespan that is, the job-shop scheduling problem can be seen simply as a sequencing problem involving all the operations that have to be performed. This motivates the approach that is presented and discussed in the following sections.

3. A Dynamic Programming approach for the job-shop scheduling problem. Held and Karp [13] presented a Dynamic Programming (DP) formulation for sequencing problems, which is famous for its application to the Traveling Salesman Problem. For this particular problem, the resulting Bellman equation is

$$\begin{cases} C(\{u\}, u) &= c_{0u} \\ C(S, u) &= \min_{v \in S \setminus \{u\}} C(S \setminus \{u\}, v) + c_{vu} \end{cases}$$

where $C(S, u)$ is the cost of the optimal path starting at 0 visiting all nodes in S and ending in u , and c_{vu} is the cost of going from v to u .

As mentioned above, the job-shop scheduling problem can be seen as a sequencing problem. Therefore, one could be tempted to use the Bellman equation above using the dominance criteria given by definition 2.3 and considering only ordered expansions.

However a small example is enough to show that the optimality principle does not hold on ordered (partial) sequences using the dominance concept introduced in the previous section. Figure 2a depicts the optimal solution for an instance of the job-shop scheduling problem with 3 jobs and 3 machines (the data can be easily retrieved from the figure). The ordered sequence defining the solution depicted is $o_1 o_3 o_6 o_2 o_5 o_4 o_9 o_7 o_8$. However, the ordered partial sequence $o_2 o_3 o_6 o_1 o_5$ which leads to the schedule depicted in Figure 2b dominates the partial sequence $o_1 o_3 o_6 o_2 o_5$ from the optimal solution.




Figure 2: Loosing optimality

In order to use the recursive equation above we propose several adjustments, which allow us to ‘restore’ the optimality principle.

3.1 Restoring the optimality guarantee. Let $S \subseteq \mathcal{O}$. Denote by $\Xi(S)$ the set of all the ordered (partial) sequences that can be associated with S (assuming that there is at least one such sequence that is, $\Xi(S) \neq \emptyset$).

Denote by $\varepsilon(S)$ the set of all operations that can be used to obtain an expansion of S . Note that $|\varepsilon(S)| \leq n$ because S can only be expanded with the first unsequenced operation in each job. Note also that if $|\varepsilon(S)| < n$, there are $n - |\varepsilon(S)|$ jobs that have all their operations already sequenced.

Denote by $\eta(T)$ the set of all operations that can be used to obtain an ordered expansion of an ordered partial sequence T . For $T \in \Xi(S)$ we have that $\eta(T) \subseteq \varepsilon(S)$. For a partial ordered sequence $T \in \Xi(S)$ let i^* denote the machine with the largest completion time (i.e. the machine determining the value $C_{\max}(T)$). In case there are multiple such machines, let i^* denote the highest-numbered machine.

For each $o \in \varepsilon(S)$ and for each $T \in \Xi(S)$ define $\psi(T, o)$ as the earliest starting time for operation o if this operation is added to the ordered partial sequence T . We have $o \in \eta(T)$ if and only if

$$\psi(T, o) + p(o) > C_{\max}(T) \wedge m(o) \leq i^* \quad \text{or} \quad \psi(T, o) + p(o) \geq C_{\max}(T) \wedge m(o) > i^*.$$

Define also

$$\xi(T, o) = \begin{cases} \psi(T, o) + p(o), & \text{if } o \in \eta(T) \\ C_{\max}(T) + p(o), & \text{otherwise.} \end{cases}$$

Note that $C_{\max}(T) \leq \xi(T, o) \leq C_{\max}(T) + p(o)$, $\forall o \in \varepsilon(S)$.

$\xi(T, o)$ represents an ‘aptitude’ value for operation o if this operation is used to expand T . In case $T + o$ is an ordered partial sequence ($o \in \eta(T)$), $\xi(T, o)$ gives the (minimum) makespan for the operations in $T + o$. Otherwise, $\xi(T, o)$ gives a loose upper bound on this makespan.

Actually $\xi(T, o)$ gives a lower bound of the completion of o in any ordered sequence that starts with T as a subsequence. For $o \in \eta(T)$ it follows directly from the definition. Otherwise, if $o \notin \eta(T)$ and o is added directly to T then $T + o$ is unordered. To add o to any (ordered) extension T' of T such that $T' + o$ is ordered, an operation o' with $m(o') = m(o)$ should be part of this extension ($T' = T + \dots + o' + \dots$). Since $T + \dots + o' + \dots$ is ordered we have $\psi(T + \dots, o') + p(o') \geq C_{\max}(T + \dots) \geq C_{\max}(T)$. Since o' and o are on the same machine we have that $\psi(T', o) \geq \psi(T + \dots, o') + p(o') \geq C_{\max}(T)$, thus $\psi(T', o) + p(o) \geq C_{\max}(T) + p(o) = \xi(T, o)$.

Denote by $\lambda(S)$ the set of operations that are the last operation of some job represented in S . Note this set only depends on the set S and not on any sequence $T \in \Xi(S)$. Taking into account this definition we always have $|\lambda(S)| \leq n$, $\forall S \subseteq \mathcal{O}$.

In order to clarify the previous concepts, we consider the instance of the job-shop scheduling problem that was introduced in Figure 2. In particular, for this instance, consider the ordered partial sequence $T = o_1 o_3 o_6 o_2 o_4$ (which leads to the schedule depicted in Figure 3a). In this case we have $C_{\max}(T) = 6$, $S = \{o_1, o_2, o_3, o_4, o_6\}$, $\varepsilon(S) = \{o_5, o_7, o_9\}$, $\lambda(S) = \{o_2, o_4, o_6\}$ and $\eta(T) = \{o_7, o_9\}$. Taking into account that $p(o_5) = 1$, $p(o_7) = 1$ and $p(o_9) = 3$ we obtain (see Figure 3b):

$$\psi(T, o_5) = 4, \psi(T, o_7) = 6, \psi(T, o_9) = 4 \quad \xi(T, o_5) = 7, \xi(T, o_7) = 7, \xi(T, o_9) = 7.$$




Figure 3: Illustration of the values $\psi(T, o)$ and $\xi(T, o)$.

Note that if we have $T' = o_1 o_3 o_6 o_2 o_5 o_4$ with $T' \in \Xi(S')$ and $S' = \{o_1, o_2, o_3, o_4, o_5, o_6\}$ we get $\lambda(S') = \{o_4, o_5, o_6\}$.

PROPOSITION 3.1 *If T_1 and T_2 are two ordered partial sequences associated with $S \subseteq \mathcal{O}$ (that is $T_1, T_2 \in \Xi(S)$) such that $\xi(T_2, o) \leq \xi(T_1, o)$, $\forall o \in \varepsilon(S)$ then any ordered expansion of T_1 is dominated by the same (possibly unordered) expansion of T_2 obtained when we add to T_2 the same operation that was added to T_1 .*

PROOF. Let $o \in \eta(T_1)$ (so that (T_1, o) is an ordered partial sequence). We have

$$\xi(T_1, o) = \psi(T_1, o) + p(o) = C_{\max}(T_1 + o) \geq C_{\max}(T_1)$$

The inequality holds because otherwise adding o to T_1 would not lead to an ordered partial solution.

Accordingly, taking into account that $\xi(T_2, o) \leq \xi(T_1, o)$ we can write $\psi(T_1, o) + p(o) \geq \xi(T_2, o)$. Therefore, either we have

$$\psi(T_1, o) + p(o) \geq \psi(T_2, o) + p(o)$$

directly, or we have

$$\psi(T_1, o) + p(o) \geq C_{\max}(T_2) + p(o) \geq \psi(T_2, o) + p(o).$$

In any case, $\psi(T_1, o) + p(o) \geq \psi(T_2, o) + p(o)$ and thereby $\psi(T_1, o) \geq \psi(T_2, o)$.

This shows that it is possible to add o to T_2 starting at time $\psi(T_1, o)$. In this case, we would obtain $C_{\max}(T_2 + o) = \psi(T_1, o) + p(o) = C_{\max}(T_1 + o)$. However, the best starting time for o when the operation is added to T_2 is $\psi(T_2, o)$ which can be lower than $\psi(T_1, o)$. In such case we would get $C_{\max}(T_2 + o) < C_{\max}(T_1 + o)$. In any case we get $C_{\max}(T_2 + o) \leq C_{\max}(T_1 + o)$, which proves the result. \square

COROLLARY 3.1 *In the conditions stated in Proposition 3.1, every ordered completion of T_1 is dominated by the same (possibly unordered) completion of T_2*

PROOF. The result follows by induction using Proposition 3.1. \square

The previous proposition and its corollary establish a means for comparing two ordered partial sequences namely, in terms of their possible expansions if done using the same operation. We introduce some additional notation. For $S \subseteq \mathcal{O}$ and $T_1, T_2 \in \Xi(S)$ when $\xi(T_2, o) \leq \xi(T_1, o), \forall o \in \varepsilon(S)$, we write $T_2 < T_1$. The reverse relation will be denoted by $>$ and equality by \doteq . Note that if $\varepsilon(S) = \emptyset$ then $T_1, T_2 \in \Xi(\mathcal{O})$ and $T_2 < T_1$ will be another way to write $C_{\max}(T_2) \leq C_{\max}(T_1)$.

The relation just established between ordered partial sequences allow us to partition the set $\Xi(S)$ into two sets, say $\hat{\Xi}(S)$ and $\Xi(S) \setminus \hat{\Xi}(S)$, such that for every $T_1 \in \hat{\Xi}(S)$, $\nexists T_2 \in \Xi(S)$ such that $T_2 < T_1$. We consider the minimal set $\hat{\Xi}(S)$ among all the possibilities that is, if two or more potential elements for being included in $\hat{\Xi}(S)$, say T_1, T_2, \dots , are such that $T_1 \doteq T_2 \doteq \dots$ then only one is chosen to be included in the set. Any rule can be defined to determine this choice. By construction, $|\hat{\Xi}(\mathcal{O})| = 1$ and it becomes clear that for every possible choice of a sequence $T \in \hat{\Xi}(\mathcal{O})$, T is optimal for the job-shop scheduling problem.

Denote by $\hat{\Xi}(S)$ the set ordered partial sequences $T \in \hat{\Xi}(S)$, such that all subsequences of T (naturally all ordered), are also elements of the set $\hat{\Xi}(\cdot)$ associated with their correspondent sets.

We have finally gathered all the ingredients that allow us to restore the optimality guarantee for the job-shop scheduling problem. The following results assure this.

PROPOSITION 3.2 *The set $\hat{\Xi}(\mathcal{O})$ is non-empty.*

PROOF. Let $T_1 \in \Xi(\mathcal{O})$ be an optimal sequence and suppose that $T_1 \notin \hat{\Xi}(\mathcal{O})$. In this case, there is at least one partial subsequence $T'_1 \in \Xi(S')$ of T_1 such that $T'_1 \notin \hat{\Xi}(S')$. Among such sequences, let \overline{T}'_1 be the one with the minimum number of operations. Then $\exists T'_2 \in \hat{\Xi}(S')$ such that $T'_2 < \overline{T}'_1$. Accordingly, we can consider the completion T_2 of T'_2 with the same operations and in the same order that is necessary to obtain T_1 from \overline{T}'_1 . We can distinguish the following cases:

- I. T_2 is ordered. This gives us two cases.
 - a) $T_2 \in \hat{\Xi}(\mathcal{O})$.
 - b) $T_2 \notin \hat{\Xi}(\mathcal{O})$. Now we can use the same procedure to find a new optimal solution T_3 . However, since $T'_2 \in \hat{\Xi}(S')$, the subsequence T''_2 of T_2 with the minimum number of operations among those such that $T''_2 \notin \hat{\Xi}(S'')$ has more operations than \overline{T}'_1 .
- II. T_2 is not ordered. We have that the ordered sequence T_2^* corresponding to the schedule defined by this completion satisfies, for all operations $o \in \mathcal{O} \setminus S'$, $\psi_{T_2^*}(o) \leq \psi_{T_1}(o)$ with strict inequality for at least one of them.

In case I.a we are finished. Case I.b increases the number of operations of the partial subsequence eventually expanded to the the optimal sequence found in case I.a. Case II. does not necessarily increase the number of operations of the partial subsequence nor decreases it. As the property stated in II. is transitive it can not include any circular relations. As case I.b increases the number of operations known of the optimal sequence $T \in \hat{\Xi}(\mathcal{O})$ to be found, the procedure of finding T may alternate between cases I.b and II. but is finite and will end in case I.a. \square

COROLLARY 3.2 *The set $\hat{\Xi}(\mathcal{O})$ contains the optimal sequence to the job-shop scheduling problem.*

PROOF. The proposition assures that $\hat{\Xi}(\mathcal{O}) \neq \emptyset$. Being non-empty, taking into account the way the set is built, we conclude that it contains a single element, which is optimal. \square

The question arising now is how can $\hat{\Xi}(\mathcal{O})$ be progressively obtained. In order to give an appropriate answer, we define $X(S)$ as the set of all ordered partial sequences $T \in \Xi(S)$ such that T is an expansion of an ordered partial sequence T' where $T = T' + o$ and $T' \in \hat{\Xi}(S \setminus \{o\})$. More formally, we define

$$X(S) = \bigcup_{o \in \lambda(S)} \bigcup_{T' \in \hat{\Xi}(S \setminus \{o\}) \text{ with } o \in \eta(T')} T' + o.$$

Define $\widehat{X}(S)$ in a similar way as done for defining $\hat{\Xi}(S)$. The following result establishes a relation between $\hat{\Xi}(S)$ and $\widehat{X}(S)$.

PROPOSITION 3.3 $\hat{\Xi}(S) = \widehat{X}(S)$.

PROOF. By definition $\hat{\Xi}(S) \supseteq \widehat{X}(S)$. Let $T \in \hat{\Xi}(S)$ and suppose $T \notin \widehat{X}(S)$ and define T' such that $T = T' + o$. Accordingly, $T' \in \hat{\Xi}(S')$ where $S' = S \setminus \{o\}$ and $T' \notin \hat{\Xi}(S')$. Since $T' \notin \hat{\Xi}(S')$ but $T' \in \hat{\Xi}(S')$ we conclude that there exists an ordered subsequence $T'' \in \Xi(S'')$ of T' for which $T'' \notin \hat{\Xi}(S'')$, so we conclude that $T \notin \hat{\Xi}(S)$ and thereby $\hat{\Xi}(S) = \widehat{X}(S)$. \square

3.2 Dynamic Programming formulation for the job-shop scheduling problem. We have finally gathered all the necessary elements to propose a Dynamic Programming approach for the job-shop scheduling problem.

Considering $\hat{\Xi}(S)$ and $\widehat{X}(S)$ ($S \subseteq \mathcal{O}$) as defined above, we can introduce the following Bellman equation for the job-shop scheduling problem:

$$\begin{cases} \hat{\Xi}(\{o\}) &= \{T\} \text{ where } T = o. \\ \hat{\Xi}(S) &= \widehat{X}(S), \quad S \subseteq \mathcal{O} \end{cases}$$

Based on this equation we propose Algorithm 3.1 for building the set $\hat{\Xi}(\mathcal{O})$ that is, to find the optimal solution to the problem.

Algorithm 3.1 Dynamic Programming for the job-shop scheduling problem

Input: An instance of the problem with n jobs and m machines
Assume: $\widehat{X}(S) = \emptyset$ for all S
Output: A sequence T associated with an optimal schedule to the problem and its makespan $C_{\max}(T)$

```

for all  $o \in \varepsilon(\emptyset)$  do
     $\widehat{X}(\{o\}) = \{T\}$  with  $T = o$ 

for  $l = 1$  to  $n * m$  do // for all sequence lengths
    for all  $S \subset \mathcal{O} : |S| = l$  do
        for all  $T_1 \in \widehat{X}(S)$  do
            for all  $o \in \eta(T)$  do
                 $T'_1 = T_1 + o$ 
                if  $T'_1 \not\preceq T_2$  for all  $T_2 \in \widehat{X}(S \cup \{o\})$  then
                    for all  $T_2 \in \widehat{X}(S \cup \{o\})$  do
                        if  $T'_1 < T_2$  then
                             $\widehat{X}(S \cup \{o\}) = \widehat{X}(S \cup \{o\}) \setminus \{T_2\}$ 
                             $\widehat{X}(S \cup \{o\}) = \widehat{X}(S \cup \{o\}) \cup \{T'_1\}$ 

```

Let T be such that $\{T\} = \hat{\Xi}(\mathcal{O})$ // $\widehat{X}(\mathcal{O}) = \hat{\Xi}(\mathcal{O})$ and $|\hat{\Xi}(\mathcal{O})| = 1$
return T and $C_{\max}(T)$

3.3 Reducing the state space. In this section we propose a reduction in the state space of our Dynamic Programming approach for the job-shop scheduling problem.

Consider the additional notation $\varepsilon(S, i) = \{o \in \varepsilon(S) : m(o) = i\}$. $\varepsilon(S, i)$ contains all the possible expansions of S that are associated with machine i ($i = 1, \dots, m$). Naturally, $\bigcup_{i=1}^m \varepsilon(S, i) = \varepsilon(S)$. The following result holds.

PROPOSITION 3.4 *Let $T \in \Xi(S)$. If $\exists i \in \{1, \dots, m\}$ such that*

$$i) \exists o^* \in \varepsilon(S, i) : i \notin \eta(T) \text{ and}$$

$$ii) \forall o \in \varepsilon(S, i), \xi(T, o) = C_{\max}(T) + p(o)$$

then there exists one optimal solution to the problem such the corresponding ordered sequence does not start with T .

PROOF. Consider that there is an optimal solution such that the corresponding ordered sequence results from a completion of T . One of the operations in the completion is o^* that appears after all operations in T . This means that in the ordered sequence associated with the optimal solution, $\psi(o^*) + p(o^*) \geq C_{\max}(T)$. However, in the conditions of the proposition it is possible to schedule o^* starting at time $\psi(T, o)$ ending in time $\psi(T, o) + p(o^*) \leq C_{\max}(T)$. With this change, it might be possible to schedule earlier the remaining operations in the completion of T . By reordering the sequence thus obtained we obtain a new ordered sequence that does not increase the optimal makespan (so is optimal) and does not have T as an ordered partial sequence. \square

REMARK 3.1 *For the operations o that satisfy the second condition of Proposition 3.4 we cannot conclude that $o \notin \eta(T)$. In fact it can be the case that $\psi(T, o) = C_{\max}(T)$.*

PROPOSITION 3.5 *If we change the definitions of $\hat{\Xi}(S)$ and $X(S)$ by removing from these sets every $T \in \Xi(S)$ satisfying Proposition 3.4, the Bellman equation still gives an optimal solution.*

PROOF. According to the conditions stated in Proposition 3.4 only possible optimal solutions are removed where it is possible to change the schedule by advancing at least a single operation (o^* as defined in Proposition 3.4). For the optimal solution found according to the proof of Proposition 3.2 no operation can be advanced without losing the feasibility of the schedule, so this optimal solution is not removed. \square

This state space reduction can be easily incorporated in Algorithm 3.1 by checking the conditions of Proposition 3.4 for each T_1 . When these conditions are satisfied do not expand T_1 any further. Note that T_1 has to be added to $\hat{X}(S)$ to enable it to discard other sequences (when $T_1 \prec T_2$).

4. Complexity analysis In this section we study the complexity of Algorithm 3.1 and present an upper bound on this complexity. In this analysis, we are not taking into account the state space reduction presented in Section 3.3, thereby also giving an upper bound for the complexity of Algorithm 3.1 with the state space reduction.

4.1 The complexity of our algorithm. Considering the main body of Algorithm 3.1 we see that the first two **for** loops together loop over all sets $S \subseteq \mathcal{O}$. This is at most 2^{nm} . As we will see below, this value can be decreased. Next there is a loop over all elements $T_1 \in \hat{\Xi}(S)$, after which all expansions $o \in \eta(T_1)$ are made. Inside these loops we have to determine $\xi(T_1', o)$ for $o \in \varepsilon(S \cup \{o\})$, and we need to compare T_1' with all $T_2 \in \hat{\Xi}(S \cup \{o\})$ which is presented in Algorithm 3.1 as looping twice but can be implemented by looping once over all elements of $\hat{\Xi}(S \cup \{o\})$. This leads to a complexity

$$O\left(2^{nm} \left| \hat{\Xi}(S) \right| |\eta(T_1)| \left(|\varepsilon(S \cup \{o\})| + \left| \hat{\Xi}(S \cup \{o\}) \right| \right)\right)$$

First we take a look into the number of subsets $S \subseteq \mathcal{O}$. Note that not all of these subsets have (feasible) ordered sequences associated with them, in which cases we have $\Xi(S) = \emptyset$. This is the case when an operation of some job is in the set but one of the preceding operations of the same job is not in the set. In fact, each job impose a sequence of precedence relations which must be respected by an ordered sequence.

This gives us n independent precedence sequences of length m . According to Gromicho et al. [11] this leads to a reduction of $\left(\frac{m+1}{2^m}\right)^n$ in the possible subsets $S \subseteq \mathcal{O}$. So we have at most $\left(\frac{m+1}{2^m}\right)^n 2^{nm} = (m+1)^n$ subsets $S \subseteq \mathcal{O}$ for which $\Xi(S) \neq \emptyset$.

Furthermore, observe that $|\eta(T_1)| \leq n$ and $|\varepsilon(S \cup \{o\})| \leq n$.

Finally we need to determine $|\hat{\Xi}(S)|$ and $|\hat{\Xi}(S \cup \{o\})|$.

Let c be the minimal value of $C_{\max}(T)$ with $T \in \hat{\Xi}(S)$ and let T_L be the sequence such that $C_{\max}(T_L) = c$. Observe that $\forall o \in \varepsilon(S)$ we have $c \leq \xi(T_L, o) \leq c + p_{\max}$. Now we have $\forall T \in \hat{\Xi}(S)$ that $C_{\max} < c + p_{\max}$, otherwise $T_L \prec T$. Hence $\forall o \in \varepsilon(S) \forall T \in \hat{\Xi}(S)$ we know that $c \leq \xi(T, o) < c + 2p_{\max}$.

Considering the values of $\xi(T, o)$, $\forall o \in \varepsilon(S)$ relative to c , we have $0 \leq \xi(T, o) - c < 2p_{\max}$. These values can be represented with a subset of the multiset $\mathcal{S} = k_1, \dots, k_n$, with $k_i = 2p_{\max} - 1$ for $i = 1, \dots, n$. \mathcal{S} consists of $k_i = 2p_{\max} - 1$ copies of n different elements x_i , $i = 1, \dots, n$, where x_i is associated with job i . Denote by $\sigma(T)$ the subset associated with T . Thus, $\sigma(T) \subseteq \mathcal{S}$ is composed by taking $\forall o \in \varepsilon(S)$, $\xi(T, o) - c$ copies of x_i where $i = j(o)$. Now observe that for $T_1, T_2 \in \Xi(S)$, $T_1 \prec T_2$ if and only if $\sigma(T_1) \subseteq \sigma(T_2)$ with $\sigma(T_1) = \sigma(T_2)$ when $T_1 \doteq T_2$. We conclude that $\forall T_1, T_2 \in \hat{\Xi}(S)$ we have $\sigma(T_1) \not\subseteq \sigma(T_2)$ and $\sigma(T_1) \not\supseteq \sigma(T_2)$.

Before proceeding our analysis, we recall the concept of an Antichain (see Anderson [2] for further details).

DEFINITION 4.1 *An Antichain is a collection of subsets of a set where no two elements of the collection are subsets of each other.*

According to this definition, the collection of $\sigma(T)$, with $T \in \hat{\Xi}(S)$, is an antichain. To make this text self-contained, we recall the following two results on antichains.

PROPOSITION 4.1 *The largest antichain in the collection of all subsets of a multiset is smaller or equal to the largest rank number N_i (N_i the number of elements with rank i).*

PROOF. See [2]. □

PROPOSITION 4.2 *The size of the largest rank for a multiset is equal to size of the middle rank λ which is*

$$N_\lambda \approx \left(\frac{2}{\pi}\right)^{\frac{1}{2}} \frac{\prod_i (k_i + 1)}{\sqrt{\frac{1}{3} \sum_i k_i (k_i + 2)}}$$

PROOF. See [2]. □

In our case we have $k_i = 2p_{\max} - 1$ for all i . Accordingly, we have $|\hat{\Xi}(S)| \approx \left(\frac{2}{\pi}\right)^{\frac{1}{2}} \frac{(2p_{\max})^n}{\sqrt{\frac{1}{3} n ((2p_{\max})^2 - 1)}}$.

Therefore,

$$|\hat{\Xi}(S)| = O \left(\frac{(2p_{\max})^n}{\sqrt{n((2p_{\max})^2 - 1)}} \right).$$

We can finally state and prove the following result.

PROPOSITION 4.3 *Algorithm 3.1 has complexity*

$$\mathcal{O} \left((2p_{\max})^{n-1} \left(n\sqrt{n} + (2p_{\max})^2 \right) (m+1)^n \right)$$

PROOF. The value obtained for $|\hat{\Xi}(S)|$ leads to the following value for the complexity of Algorithm 3.1.

$$O \left(\left(\frac{(2p_{\max})^n}{\sqrt{n((2p_{\max})^2 - 1)}} + n \right) \frac{n(2p_{\max})^n}{\sqrt{n((2p_{\max})^2 - 1)}} (m+1)^n \right)$$

From here we obtain successively

$$\begin{aligned}
& \mathcal{O} \left(\left(\frac{(2p_{\max})^n}{\sqrt{n(2p_{\max})^2}} + n \right) \frac{n(2p_{\max})^n}{\sqrt{n(2p_{\max})^2}} (m+1)^n \right) \\
& \mathcal{O} \left(\left(\frac{(2p_{\max})^{n-1}}{\sqrt{n}} + n \right) \frac{n(2p_{\max})^{n-1}}{\sqrt{n}} (m+1)^n \right) \\
& \mathcal{O} \left(((2p_{\max})^{2n-2} + n\sqrt{n}(2p_{\max})^{n-1}) (m+1)^n \right) \\
& \mathcal{O} \left((2p_{\max})^{n-1} (n\sqrt{n} + (2p_{\max})^2) (m+1)^n \right)
\end{aligned}$$

□

With the analysis above, we were able to give an upper bound on $|\hat{\Xi}(S)|$ with $S \subseteq \mathcal{O}$. This results in an upper bound on the complexity of Algorithm 3.1. Note, however, that the actual value of $|\hat{\Xi}(S)|$ is much lower and thus we strongly suspect that the actual complexity of our procedure is much lower. This is also evidenced by the computational results presented in section 5. Nevertheless, the value achieved represents already an important breakthrough as we show next.

4.2 Comparison with brute force. The following results holds.

PROPOSITION 4.4 *For a fixed p_{\max} , the Dynamic Programming approach that we propose for the job-shop scheduling problem has a complexity that is exponentially smaller than brute-force in n and in m .*

PROOF. Using Stirling's approximation¹ we can evaluate the ratio between the complexity associated with brute-force and the complexity of our procedure. We have:

$$\begin{aligned}
\frac{(n!)^m}{(2p_{\max})^{n-1} (n\sqrt{n} + (2p_{\max})^2) (m+1)^n} & \approx \frac{(\sqrt{2\pi n} \left(\frac{n}{e}\right)^n)^m}{(2p_{\max})^{n-1} (n\sqrt{n} + (2p_{\max})^2) (m+1)^n} \\
& \approx \frac{2p_{\max}\sqrt{2\pi n}^m}{(2p_{\max})^2 + n\sqrt{n}} \left(\frac{\left(\frac{n}{e}\right)^m}{2p_{\max}(m+1)} \right)^n
\end{aligned}$$

This is clearly exponential in m , but is only exponential in n if $\frac{(\frac{n}{e})^m}{2p_{\max}(m+1)} > 1$, or equivalently. if $\left(\frac{n}{e}\right)^m > 2p_{\max}(m+1)$. Accordingly, for a fixed p_{\max} the result holds. □

This result represents an important breakthrough because it shows that the new algorithm solves the job-shop scheduling problem with a complexity exponentially lower than 'brute force'.

5. Computational analysis. In order to evaluate our complexity analysis of the new algorithm, we run some computational tests considering benchmark instances for the job-shop scheduling problem. In particular we considered instances *ft06* and *la01-la05*. The first instance was first proposed by Fisher and Thompson [9]. The other five were proposed by Lawrence [18]. These benchmark instances (among many others) are available in the OR Library [23].

We implemented the new algorithm including the state space reduction of Section 3.3 with C++ and the tests were performed on a windows 64 bit machine with a 2.66 GHz CPU and 8 GB memory.

In Table 1 we can observe the results obtained. In this table, the first three columns contain the information defining the instance namely, the name, the number of jobs (n) and the number of machines (m). Columns 4 and 5 depict the computational resources requirements for the instances considered. In particular we present the CPU time in seconds for solving each instance as well as the memory required. Columns 6-9 contain the observed and estimated values for the maximal size of $\hat{\Xi}(S)$ ($\max_S |\hat{\Xi}(S)|$) and

for the total number of sequences in the state space ($|\bigcup_S \hat{\Xi}(S)|$).

¹ $n! \approx \sqrt{2\pi n} \left(\frac{n}{e}\right)^n$

Instance	Size		Resources		Observed		Estimated	
	n	m	CPU time	Memory	$\max_S \hat{\Xi}(S) $	$ \bigcup_S \hat{\Xi}(S) $	$\max_S \hat{\Xi}(S) $	$ \bigcup_S \hat{\Xi}(S) $
<i>ft06</i>	6	6	< 1 s	2 MB	13	30.409	$1.308 \cdot 10^3$	$153.888 \cdot 10^6$
<i>la01</i>	10	5	1533 s	1922 MB	142	63.170.946	$134.992 \cdot 10^{15}$	$8.162 \cdot 10^{24}$
<i>la02</i>	10	5	1961 s	2313 MB	157	80.862.876	$147.908 \cdot 10^{15}$	$8.943 \cdot 10^{24}$
<i>la03</i>	10	5	1206 s	1400 MB	191	50.910.284	$69.286 \cdot 10^{15}$	$4.189 \cdot 10^{24}$
<i>la04</i>	10	5	1629 s	2023 MB	113	68.208.819	$134.992 \cdot 10^{15}$	$8.162 \cdot 10^{24}$
<i>la05</i>	10	5	965 s	1321 MB	182	40.229.147	$123.089 \cdot 10^{15}$	$7.442 \cdot 10^{24}$

Table 1: Computational results


As we can see, the number of sequences needed to solve each instance is much smaller than the estimation obtained in section 4, which gives strong evidence that the bounds presented in the previous section can be improved significantly. For the first instance we were able to run our algorithm without the state space reduction using 2.6 seconds and 8 MB, having values 16 and 190592 for $\max_S |\hat{\Xi}(S)|$ and $|\bigcup_S \hat{\Xi}(S)|$ respectively. According to these values even without state space reduction our complexity analysis is still very conservative.

We should stress here that although using an exponential amount of memory our algorithm can be implemented in such way that only the optimal value is found saving a constant factor in memory. Nevertheless, for the instances that we could run not only the optimal value but also an optimal solution was found.

We present our algorithm as one to find the optimal sequence of operations. From this sequence the optimal solution immediately follows. For example, in the case of instance *ft06* we obtained the following optimal sequence:

$o_3 o_1 o_2 o_7 o_9 o_4 o_8 o_6 o_{15} o_{10} o_{12} o_{13} o_5 o_{14} o_{11} o_{21} o_{16} o_{27} o_{18} o_{22} o_{17} o_{19} o_{24} o_{28} o_{20} o_{25} o_{30} o_{36} o_{23}$
 $o_{26} o_{31} o_{29} o_{32} o_{35} o_{34} o_{33}$

This sequence corresponds with the solution in Figure 4. This solution has the well-known optimal value of 55 (see for instance [15]).

Figure 4: Optimal solution of *ft06*

6. Conclusion. In this paper we proposed a Dynamic Programming approach for the classical job-shop scheduling problem. The main achievements of this paper are twofold:

- (i) We produce an optimal algorithm with complexity proven to be exponentially lower than exhaustive enumeration, which is to date the best complexity guarantee of an optimal algorithm for the job-shop scheduling problem that we are aware of. Furthermore, our complexity analysis is extremely conservative and our results show strong empirical evidence that they may be improved by a few orders of magnitude.
- (ii) Despite the theoretical interest, our algorithm proves to work in practice by solving some moderate benchmark instances.

References

- [1] J. Adams, E. Balas, and D. Zawack, *The shifting bottleneck procedure for job shop scheduling*, Management Science **34** (1988), 391–401.
- [2] I. Anderson, *Combinatorics of finite sets*, Dover Publications, Inc., 1987.
- [3] D. Applegate and W. Cook, *A computational study of job-shop scheduling*, ORSA Journal of Computing **3** (1991), 149–156.
- [4] P. Brucker, B. Jurisch, and B. Sievers, *A branch and bound algorithm for the job-shop scheduling problem*, Discrete Applied Mathematics **49** (1994), 109–127.
- [5] J. Carlier and E. Pinson, Management Science **35** (1989), 164–176.
- [6] F.D. Croce, R. Tadei, and G. Volta, *A genetic algorithm for the job shop problem*, Computers & Operations Research **22** (1995), 15–24.
- [7] U. Dorndorf and E. Pesch, *Evolution based learning in a job shop scheduling environment*, Computers & Operations Research **22** (1995), 25–40.
- [8] U. Feige and C. Scheideler, *Improved bounds for acyclic job shop scheduling*, Proceedings of the 30st Annual ACM Symposium on the Theory of Computing, 1998, pp. 624–633.
- [9] H. Fisher and G. L. Thompson, *Probabilistic learning combinations of local job-shop scheduling rules*, Industrial Scheduling (J.F. Muth and G.L. Thompson, eds.), Prentice Hall, Englewood Cliffs, New Jersey, 1963, p. 225.
- [10] L.A. Goldberg, M. Paterson, A. Srinivasan, and E. Sweedyk, *Better approximation guarantees for jobshop scheduling*, Proceedings of the 8th Symposium on Discrete Algorithms, 1997, pp. 599–608.
- [11] J.A.S. Gromicho, J.J.van Hoorn, A.L. Kok, and J.M.J. Schutten, *Restricted dynamic programming: a flexible framework for solving realistic vrps*, Tech. Report 266, University Of Twente, The Netherlands, 2008, submitted.
- [12] N. Hefetz and I. Adiri, *An efficient optimal algorithm for the two-machines unit-time jobshop schedule-length problem*, Mathematics of Operations Research **7** (1982), 354–360.
- [13] M. Held and R.M. Karp, *A dynamic programming approach to sequencing problems*, SIAM J. Appl. Math. **10** (1962), 196–210.
- [14] J. R. Jackson, *Scheduling a production line to minimize maximum tardiness*, Tech. report, Management Science Research Project, University of California. Los Angeles, 1955.
- [15] A.S. Jain and S. Meeran, *Deterministic job-shop scheduling: Past, present and future*, European Journal of Operational Research **113** (1999), 390–434.
- [16] K. Jansen, R. Solis-Oba, and M.I. Sviridenko, *Makespan minimization in job shops: A polynomial time approximation scheme*, Proceedings of the 31st Annual ACM Symposium on the Theory of Computing, 1999, pp. 418–426.
- [17] B.J. Lageweg, J.K.Lenstra, and A.H.G. Rinnooy Kan, *Job-shop scheduling by implicit enumeration*, Management Science **24** (1977), 441–450.
- [18] S. Lawrence, *Resource constrained project scheduling. an experimental investigation of heuristic scheduling techniques*, GSIA, Carnegie-Mellon University, 1984.
- [19] F.T. Leighton, B.M. Maggs, and S.B. Rao, *Packet routing and job shop scheduling in $O(\text{congestion} + \text{dilation})$ steps*, Combinatorica **14** (1994), 167–186.

- [20] F.T. Leighton, B.M. Maggs, and A. Richa, *Fast algorithms for finding $O(\text{congestion} + \text{dilation})$ packet routing schedules*, Technical Report CMU-CS-96-152, School of Computer Science, Carnegie Mellon University, Pittsburgh, USA, 1996.
- [21] J. K. Lenstra and A. H. G. Rinnooy Kan, *Computational complexity of discrete optimization problems.*, Annals of Discrete Mathematics **4** (1979), 121–140.
- [22] J. K. Lenstra, A. H. G. Rinnooy Kan, and P. Brucker, *Complexity of machine scheduling problems.*, Annals of Discrete Mathematics **1** (1977), 343–362.
- [23] OR Library, <http://people.brunel.ac.uk/~mastjjb/jeb/info.html>, 2009.
- [24] Paul Martin and David B. Shmoys, *A new approach to computing optimal schedules for the job-shop scheduling problem*, Proceedings of the 5th International IPCO Conference on Integer Programming and Combinatorial Optimization (London, UK), Springer-Verlag, 1996, pp. 389–403.
- [25] E. Nowicki and C. Smutnicki, *A fast taboo search algorithm for the job shop scheduling problem*.
- [26] C. Rego and R. Duarte, *A filter-and-fan approach to the job shop scheduling problem*, European Journal of Operational Research **194** (2009), 650–662.
- [27] D.B. Shmoys, C. Stein, and J. Wein, *Improved approximation algorithms for shop scheduling problems problems*, SIAM Journal of Computing **23** (1994), 617–632.
- [28] K. Steinhöfel, A. Albrecht, and C.K. Wong, *Two simulated annealing-based heuristics for the job shop scheduling problem*, European Journal of Operational Research **118** (1999), 524–548.
- [29] E.D. Taillard, *Parallel taboo search techniques for the job-shop scheduling problem*, ORSA Journal on Computing **6** (1994), 108–117.
- [30] P.J.M. Van Laarhoven, E.H.L. Aarts, and J.K. Lenstra, *Job shop scheduling by simulated annealing*, Operations Research **40** (1992), 113–125.
- [31] G. J. Woeginger, *Exact algorithms for NP-hard problems: a survey*, Combinatorial optimization - Eureka, you shrink! (Michael Jünger, Gerhard Reinelt, and Giovanni Rinaldi, eds.), Springer-Verlag New York, Inc., New York, NY, USA, 2003, pp. 185–207.
- [32] ———, *Open problems around exact algorithms*, Discrete Appl. Math. **156** (2008), no. 3, 397–405.
- [33] C. Y. Zhang, P.-G. Li, Y.-Q. Rao, and Z.-L. Guan, *A very fast TS/SA algorithm for the job shop scheduling problem*, Computers & Operations Research **35** (2008), 282–294.

2005-1	Meindert Flikkema	Exploring service development for understanding Schumpeterian Innovation in service firms: the deduction of special case criteria, pp. 43
2005-2	Enno Masurel	Use of Patent Information: Empirical Evidence from Innovative SME's, pp. 18
2005-3	Rutger Kroon Iris F.A. Vis	Seriously Ceres?, pp. 23
2005-4	Lidewey van der Sluis Leon de Caluwé Antonie van Nistelrooij	An explorative analysis of the links between learning behavior and change orientation, pp. 18
2005-5	F.A.G. den Butter O.K. van Megchelen	Uitbesteden en innovatie in de bouw Het toenemend belang van de regie- en handelsfunctie, pp. 10
2005-6	Adriaan J. van der Welle Frank A.G. den Butter	Arbeidsmarktflexibiliteit in de EMU: een beleidsgericht literatuuroverzicht, pp. 31
2005-7	Marina van Geenhuizen Peter Nijkamp	Death of distance and agglomeration forces of firms in the urban E-economy An artificial intelligence approach using rough set analysis, pp. 23
2005-8	Iris F.A. Vis Maurice Bakker	Dispatching and layout rules at an automated container terminal, pp. 17
2005-9	M. Francesca Cracolici Peter Nijkamp	Attractiveness and Effectiveness of Competing Tourist Areas: A Study on Italian Provinces, pp. 53
2005-10	Tibert Verhagen Jaap Boter	The importance of website content in online purchasing across different types of products, pp. 28
2005-11	Marina van Geenhuizen Peter Nijkamp	Place-bound versus Footloose Firms in a Metropolitan Area, pp. 17
2005-12	J.M. van Sonsbeek R.H.J.M. Gradus	A microsimulation analysis of the 2006 regime change in the Dutch disability scheme, pp. 29
2005-13	Kim A.D. Treur Lidewey E.C. van der Sluis	The benefits of coaching for employees and their organizations, pp. 30
2005-14	Wim den Dekker Paul G.W. Jansen Claartje J. Vinkenburg	Dimensions of an individual global mindset, pp. 29

2006-1	Tibert Verhagen Selmar Meents Yao-Hua Tan	Perceived risk and trust associated with purchasing at Electronic Marketplaces, 39 p.
2006-2	Mediha Sahin Marius Rietdijk Peter Nijkamp	Ethnic employees' behaviour vis-à-vis customers in the service sector, 17 p.
2006-3	Albert J. Menkveld	Splitting orders in overlapping markets: A study of cross-listed stocks, 45 p.
2006-4	Kalok Chan Albert J. Menkveld Zhishu Yang	Are domestic investors better informed than foreign investors? Evidence from the perfectly segmented market in China, 33 p.
2006-5	Kalok Chan Albert J. Menkveld Zhishu Yang	Information asymmetry and asset prices: Evidence from the China foreign share discount, 38 p.
2006-6	Albert J. Menkveld Yiu C. Cheung Frank de Jong	Euro-area sovereign yield dynamics: The role of order imbalance, 34 p.
2006-7	Frank A.G. den Butter	The industrial organisation of economic policy preparation in the Netherlands
2006-8	Evgenia Motchenkova	Cost minimizing sequential punishment policies for repeat offenders, 20 p.
2006-9	Ginés Hernández- Cánovas Johanna Koëter- Kant	SME Financing in Europe: Cross-country determinants of debt maturity, 30 p.
2006-10	Pieter W. Jansen	Did capital market convergence lower the effectiveness of the interest rate as a monetary policy tool? 17 p.
2006-11	Pieter W. Jansen	Low inflation, a high net savings surplus and institutional restrictions keep the long-term interest rate low. 24 p.
2006-12	Joost Baeten Frank A.G. den Butter	Welfare gains by reducing transactions costs: Linking trade and innovation policy, 28 p.
2006-13	Frank A.G. den Butter Paul Wit	Trade and product innovations as sources for productivity increases: an empirical analysis, 21 p.
2006-14	M. Francesca Cracolici Miranda Cuffaro Peter Nijkamp	Sustainable tourist development in Italian Holiday destination, 10 p.

2006-15	Simonetta Longhi Peter Nijkamp	Forecasting regional labor market developments under spatial heterogeneity and spatial correlation, 25 p
2006-16	Mediha Sahin Peter Nijkamp Tüzin Baycan-Levent	Migrant Entrepreneurship from the perspective of cultural diversity, 21 p.
2006-17	W.J. Wouter Botzen Philip S. Marey	Does the ECB respond to the stock market? 23 p.
2006-18	Tüzin Baycan-Levent Peter Nijkamp	Migrant female entrepreneurship: Driving forces, motivation and performance, 31 p.
2006-19	Ginés Hernández-Cánovas Johanna Koëter-Kant	The European institutional environment and SME relationship lending: Should we care? 24 p.
2006-20	Miranda Cuffaro Maria Francesca Cracolici Peter Nijkamp	Economic convergence versus socio-economic convergence in space, 13 p.
2006-21	Mediha Sahin Peter Nijkamp Tüzin Baycan-Levent	Multicultural diversity and migrant entrepreneurship: The case of the Netherlands, 29 p.

2007-1	M. Francesca Cracolici Miranda Cuffaro Peter Nijkamp	Geographical distribution of enemployment: An analysis of provincial differences in Italy, 21 p.
2007-2	Daniel Leliefeld Evgenia Motchenkova	To protect in order to serve, adverse effects of leniency programs in view of industry asymmetry, 29 p.
2007-3	M.C. Wassenaar E. Dijkgraaf R.H.J.M. Gradus	Contracting out: Dutch municipalities reject the solution for the VAT-distortion, 24 p.
2007-4	R.S. Halbersma M.C. Mikkers E. Motchenkova I. Seinen	Market structure and hospital-insurer bargaining in the Netherlands, 20 p.
2007-5	Bas P. Singer Bart A.G. Bossink Herman J.M. Vande Putte	Corporate Real estate and competitive strategy, 27 p.
2007-6	Dorien Kooij Annet de Lange Paul Jansen Josje Dijkers	Older workers' motivation to continue to work: Five meanings of age. A conceptual review, 46 p.
2007-7	Stella Flytzani Peter Nijkamp	Locus of control and cross-cultural adjustment of expatriate managers, 16 p.
2007-8	Tibert Verhagen Willemijn van Dolen	Explaining online purchase intentions: A multi-channel store image perspective, 28 p.
2007-9	Patrizia Riganti Peter Nijkamp	Congestion in popular tourist areas: A multi-attribute experimental choice analysis of willingness-to-wait in Amsterdam, 21 p.
2007-10	Tüzin Baycan-Levent Peter Nijkamp	Critical success factors in planning and management of urban green spaces in Europe, 14 p.
2007-11	Tüzin Baycan-Levent Peter Nijkamp	Migrant entrepreneurship in a diverse Europe: In search of sustainable development, 18 p.
2007-12	Tüzin Baycan-Levent Peter Nijkamp Mediha Sahin	New orientations in ethnic entrepreneurship: Motivation, goals and strategies in new generation ethnic entrepreneurs, 22 p.
2007-13	Miranda Cuffaro Maria Francesca Cracolici Peter Nijkamp	Measuring the performance of Italian regions on social and economic dimensions, 20 p.

2007-14	Tüzin Baycan-Levent Peter Nijkamp	Characteristics of migrant entrepreneurship in Europe, 14 p.
2007-15	Maria Teresa Borzacchiello Peter Nijkamp Eric Koomen	Accessibility and urban development: A grid-based comparative statistical analysis of Dutch cities, 22 p.
2007-16	Tibert Verhagen Selmar Meents	A framework for developing semantic differentials in IS research: Assessing the meaning of electronic marketplace quality (EMQ), 64 p.
2007-17	Aliye Ahu Gülümser Tüzin Baycan Levent Peter Nijkamp	Changing trends in rural self-employment in Europe, 34 p.
2007-18	Laura de Dominicis Raymond J.G.M. Florax Henri L.F. de Groot	De ruimtelijke verdeling van economische activiteit: Agglomeratie- en locatiepatronen in Nederland, 35 p.
2007-19	E. Dijkgraaf R.H.J.M. Gradus	How to get increasing competition in the Dutch refuse collection market? 15 p.

2008-1	Maria T. Borzacchiello Irene Casas Biagio Ciuffo Peter Nijkamp	Geo-ICT in Transportation Science, 25 p.
2008-2	Maura Soekijad Jeroen Walschots Marleen Huysman	Congestion at the floating road? Negotiation in networked innovation, 38 p.
2008-3	Marlous Agterberg Bart van den Hooff Marleen Huysman Maura Soekijad	Keeping the wheels turning: Multi-level dynamics in organizing networks of practice, 47 p.
2008-4	Marlous Agterberg Marleen Huysman Bart van den Hooff	Leadership in online knowledge networks: Challenges and coping strategies in a network of practice, 36 p.
2008-5	Bernd Heidergott Haralambie Leahu	Differentiability of product measures, 35 p.
2008-6	Tibert Verhagen Frans Feldberg Bart van den Hooff Selmar Meents	Explaining user adoption of virtual worlds: towards a multipurpose motivational model, 37 p.
2008-7	Masagus M. Ridhwan Peter Nijkamp Piet Rietveld Henri L.F. de Groot	Regional development and monetary policy. A review of the role of monetary unions, capital mobility and locational effects, 27 p.
2008-8	Selmar Meents Tibert Verhagen	Investigating the impact of C2C electronic marketplace quality on trust, 69 p.
2008-9	Junbo Yu Peter Nijkamp	China's prospects as an innovative country: An industrial economics perspective, 27 p
2008-10	Junbo Yu Peter Nijkamp	Ownership, r&d and productivity change: Assessing the catch-up in China's high-tech industries, 31 p
2008-11	Elbert Dijkgraaf Raymond Gradus	Environmental activism and dynamics of unit-based pricing systems, 18 p.
2008-12	Mark J. Koetse Jan Rouwendal	Transport and welfare consequences of infrastructure investment: A case study for the Betuweroute, 24 p
2008-13	Marc D. Bahlmann Marleen H. Huysman Tom Elfring Peter Groenewegen	Clusters as vehicles for entrepreneurial innovation and new idea generation – a critical assessment
2008-14	Soushi Suzuki Peter Nijkamp	A generalized goals-achievement model in data envelopment analysis: An application to efficiency improvement in local government finance in Japan, 24 p.
2008-15	Tüzin Baycan-Levent	External orientation of second generation migrant entrepreneurs. A sectoral

	Peter Nijkamp Mediha Sahin	study on Amsterdam, 33 p.
2008-16	Enno Masurel	Local shopkeepers' associations and ethnic minority entrepreneurs, 21 p.
2008-17	Frank Frößler Boriana Rukanova Stefan Klein Allen Higgins Yao-Hua Tan	Inter-organisational network formation and sense-making: Initiation and management of a living lab, 25 p.
2008-18	Peter Nijkamp Frank Zwetsloot Sander van der Wal	A meta-multicriteria analysis of innovation and growth potentials of European regions, 20 p.
2008-19	Junbo Yu Roger R. Stough Peter Nijkamp	Governing technological entrepreneurship in China and the West, 21 p.
2008-20	Maria T. Borzacchiello Peter Nijkamp Henk J. Scholten	A logistic regression model for explaining urban development on the basis of accessibility: a case study of Naples, 13 p.
2008-21	Marius Ooms	Trends in applied econometrics software development 1985-2008, an analysis of Journal of Applied Econometrics research articles, software reviews, data and code, 30 p.
2008-22	Aliye Ahu Gülümser Tüzin Baycan-Levent Peter Nijkamp	Changing trends in rural self-employment in Europe and Turkey, 20 p.
2008-23	Patricia van Hemert Peter Nijkamp	Thematic research prioritization in the EU and the Netherlands: an assessment on the basis of content analysis, 30 p.
2008-24	Jasper Dekkers Eric Koomen	Valuation of open space. Hedonic house price analysis in the Dutch Randstad region, 19 p.

2009-1	Boriana Rukanova Rolf T. Wignand Yao-Hua Tan	From national to supranational government inter-organizational systems: An extended typology, 33 p.
2009-2	Marc D. Bahlmann Marleen H. Huysman Tom Elfring Peter Groenewegen	Global Pipelines or global buzz? A micro-level approach towards the knowledge-based view of clusters, 33 p.
2009-3	Julie E. Ferguson Marleen H. Huysman	Between ambition and approach: Towards sustainable knowledge management in development organizations, 33 p.
2009-4	Mark G. Leijssen	Why empirical cost functions get scale economies wrong, 11 p.
2009-5	Peter Nijkamp Galit Cohen-Blankshtain	The importance of ICT for cities: e-governance and cyber perceptions, 14 p.
2009-6	Eric de Noronha Vaz Mário Caetano Peter Nijkamp	Trapped between antiquity and urbanism. A multi-criteria assessment model of the greater Cairo metropolitan area, 22 p.
2009-7	Eric de Noronha Vaz Teresa de Noronha Vaz Peter Nijkamp	Spatial analysis for policy evaluation of the rural world: Portuguese agriculture in the last decade, 16 p.
2009-8	Teresa de Noronha Vaz Peter Nijkamp	Multitasking in the rural world: Technological change and sustainability, 20 p.
2009-9	Maria Teresa Borzacchiello Vincenzo Torrieri Peter Nijkamp	An operational information systems architecture for assessing sustainable transportation planning: Principles and design, 17 p.
2009-10	Vincenzo Del Giudice Pierfrancesco De Paola Francesca Torrieri Francesca Pagliari Peter Nijkamp	A decision support system for real estate investment choice, 16 p.
2009-11	Miruna Mazurencu Marinescu Peter Nijkamp	IT companies in rough seas: Predictive factors for bankruptcy risk in Romania, 13 p.
2009-12	Boriana Rukanova Helle Zinner Hendriksen Eveline van Stijn Yao-Hua Tan	Bringing is innovation in a highly-regulated environment: A collective action perspective, 33 p.
2009-13	Patricia van Hemert Peter Nijkamp Jolanda Verbraak	Evaluating social science and humanities knowledge production: an exploratory analysis of dynamics in science systems, 20 p.

2009-14	Roberto Patuelli Aura Reggiani Peter Nijkamp Norbert Schanne	Neural networks for cross-sectional employment forecasts: A comparison of model specifications for Germany, 15 p.
2009-15	André de Waal Karima Kourtit Peter Nijkamp	The relationship between the level of completeness of a strategic performance management system and perceived advantages and disadvantages, 19 p.
2009-16	Vincenzo Punzo Vincenzo Torrieri Maria Teresa Borzacchiello Biagio Ciuffo Peter Nijkamp	Modelling intermodal re-balance and integration: planning a sub-lagoon tube for Venezia, 24 p.
2009-17	Peter Nijkamp Roger Stough Mediha Sahin	Impact of social and human capital on business performance of migrant entrepreneurs – a comparative Dutch-US study, 31 p.
2009-18	Dres Creal	A survey of sequential Monte Carlo methods for economics and finance, 54 p.
2009-19	Karima Kourtit André de Waal	Strategic performance management in practice: Advantages, disadvantages and reasons for use, 15 p.
2009-20	Karima Kourtit André de Waal Peter Nijkamp	Strategic performance management and creative industry, 17 p.
2009-21	Eric de Noronha Vaz Peter Nijkamp	Historico-cultural sustainability and urban dynamics – a geo-information science approach to the Algarve area, 25 p.
2009-22	Roberta Capello Peter Nijkamp	Regional growth and development theories revisited, 19 p.
2009-23	M. Francesca Cracolici Miranda Cuffaro Peter Nijkamp	Tourism sustainability and economic efficiency – a statistical analysis of Italian provinces, 14 p.
2009-24	Caroline A. Rodenburg Peter Nijkamp Henri L.F. de Groot Erik T. Verhoef	Valuation of multifunctional land use by commercial investors: A case study on the Amsterdam Zuidas mega-project, 21 p.
2009-25	Katrin Oltmer Peter Nijkamp Raymond Florax Floor Brouwer	Sustainability and agri-environmental policy in the European Union: A meta-analytic investigation, 26 p.
2009-26	Francesca Torrieri Peter Nijkamp	Scenario analysis in spatial impact assessment: A methodological approach, 20 p.
2009-27	Aliye Ahu Gülümser Tüzin Baycan-Levent Peter Nijkamp	Beauty is in the eyes of the beholder: A logistic regression analysis of sustainability and locality as competitive vehicles for human settlements, 14 p.

2009-28	Marco Percoco Peter Nijkamp	Individual time preferences and social discounting in environmental projects, 24 p.
2009-29	Peter Nijkamp Maria Abreu	Regional development theory, 12 p.
2009-30	Tüzin Baycan-Levent Peter Nijkamp	7 FAQs in urban planning, 22 p.
2009-31	Aliye Ahu Gülümser Tüzin Baycan-Levent Peter Nijkamp	Turkey's rurality: A comparative analysis at the EU level, 22 p.
2009-32	Frank Bruinsma Karima Kourtit Peter Nijkamp	An agent-based decision support model for the development of e-services in the tourist sector, 21 p.
2009-33	Mediha Sahin Peter Nijkamp Marius Rietdijk	Cultural diversity and urban innovativeness: Personal and business characteristics of urban migrant entrepreneurs, 27 p.
2009-34	Peter Nijkamp Mediha Sahin	Performance indicators of urban migrant entrepreneurship in the Netherlands, 28 p.
2009-35	Manfred M. Fischer Peter Nijkamp	Entrepreneurship and regional development, 23 p.
2009-36	Faroek Lazrak Peter Nijkamp Piet Rietveld Jan Rouwendal	Cultural heritage and creative cities: An economic evaluation perspective, 20 p.
2009-37	Enno Masurel Peter Nijkamp	Bridging the gap between institutions of higher education and small and medium-size enterprises, 32 p.
2009-38	Francesca Medda Peter Nijkamp Piet Rietveld	Dynamic effects of external and private transport costs on urban shape: A morphogenetic perspective, 17 p.
2009-39	Roberta Capello Peter Nijkamp	Urban economics at a cross-yard: Recent theoretical and methodological directions and future challenges, 16 p.
2009-40	Enno Masurel Peter Nijkamp	The low participation of urban migrant entrepreneurs: Reasons and perceptions of weak institutional embeddedness, 23 p.
2009-41	Patricia van Hemert Peter Nijkamp	Knowledge investments, business R&D and innovativeness of countries. A qualitative meta-analytic comparison, 25 p.
2009-42	Teresa de Noronha Vaz Peter Nijkamp	Knowledge and innovation: The strings between global and local dimensions of sustainable growth, 16 p.
2009-43	Chiara M. Traversi Peter Nijkamp	Managing environmental risk in agriculture: A systematic perspective on the potential of quantitative policy-oriented risk valuation, 19 p.
2009-44	Sander de Leeuw	Logistics aspects of emergency preparedness in flood disaster prevention, 24 p.

Iris F.A. Vis
Sebastiaan B. Jonkman

- | | | |
|---------|-----------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| 2009-45 | Eveline S. van Leeuwen
Peter Nijkamp | Social accounting matrices. The development and application of SAMs at the local level, 26 p. |
| 2009-46 | Tibert Verhagen
Willemijn van Dolen | The influence of online store characteristics on consumer impulsive decision-making: A model and empirical application, 33 p. |
| 2009-47 | Eveline van Leeuwen
Peter Nijkamp | A micro-simulation model for e-services in cultural heritage tourism, 23 p. |
| 2009-48 | Andrea Caragliu
Chiara Del Bo
Peter Nijkamp | Smart cities in Europe, 15 p. |
| 2009-49 | Farook Lazrak
Peter Nijkamp
Piet Rietveld
Jan Rouwendal | Cultural heritage: Hedonic prices for non-market values, 11 p. |
| 2009-50 | Eric de Noronha Vaz
João Pedro Bernardes
Peter Nijkamp | Past landscapes for the reconstruction of Roman land use: Eco-history tourism in the Algarve, 23 p. |
| 2009-51 | Eveline van Leeuwen
Peter Nijkamp
Teresa de Noronha Vaz | The Multi-functional use of urban green space, 12 p. |
| 2009-52 | Peter Bakker
Carl Koopmans
Peter Nijkamp | Appraisal of integrated transport policies, 20 p. |
| 2009-53 | Luca De Angelis
Leonard J. Paas | The dynamics analysis and prediction of stock markets through the latent Markov model, 29 p. |
| 2009-54 | Jan Anne Annema
Carl Koopmans | Een lastige praktijk: Ervaringen met waarderen van omgevingskwaliteit in de kosten-batenanalyse, 17 p. |
| 2009-55 | Bas Straathof
Gert-Jan Linders | Europe's internal market at fifty: Over the hill? 39 p. |
| 2009-56 | Joaquim A.S. Gromicho
Jelke J. van Hoorn
Francisco Saldanha-da-Gama
Gerrit T. Timmer | Exponentially better than brute force: solving the job-shop scheduling problem optimally by dynamic programming, 14 p. |